



Product Service

CERTIFICATE

No. Z2 083334 0052 Rev. 03

Model(s):

Full cell 1000 V DC system voltage Single Glass modules:

UL-xxxM-72, xxx= 330 to 390 in step of 5;

UL-xxxM-60, xxx= 275 to 325 in step of 5;

UL-xxxM-54, xxx= 245 to 290 in step of 5;

Half cell 1000 V DC system voltage Single Glass modules:

UL-xxxM-144, xxx= 370 to 415 in step of 5;

UL-xxxM-120, xxx= 305 to 345 in step of 5;

UL-xxxM-108, xxx= 275 to 315 in step of 5;

UL-xxxM-144, xxx= 430 to 450 in step of 5;

UL-xxxM-120, xxx= 360 to 375 in step of 5;

UL-xxxM-108, xxx= 325 to 335 in step of 5;

Half cell 1500 V DC system voltage Single Glass modules:

UL-xxxM-144HV, xxx= 370 to 415 in step of 5;

UL-xxxM-120HV, xxx= 305 to 345 in step of 5;

UL-xxxM-108HV, xxx= 275 to 315 in step of 5;

UL-xxxM-144HV, xxx= 430 to 450 in step of 5;

UL-xxxM-120HV, xxx= 360 to 375 in step of 5;

UL-xxxM-108HV, xxx= 325 to 335 in step of 5;

xxx is standing for rated output power at STC

Parameters:

Construction:	Framed, with Junction box, Cable and Connectors.
Safety Class:	Class II
Maximum System Voltage:	1000 V DC or 1500 V DC
Fire Safety Class:	Class C according to UL 790
PID Test Condition:	-1500V DC, 96h, 85% RH, 85°C

Tested according to:

IEC 61215-1(ed.1)
IEC 61215-1-1(ed.1)
IEC 61215-2(ed.1)
IEC 61730-1(ed.2)
IEC 61730-2(ed.2)
PPP 58042B:2015

Production Facility(ies):

083334

ZERTIFIKAT • CERTIFICATE • 認證證書 • CERTIFICADO • CERTIFICAT